

- Easy programming using selection button sequence
- Electronic control and data-recording
- Thermostatically controlled forced air-cooling
- Each column has individual vend motor
- 24 V D/C motors
- Interchangeable parts
- One-piece inner door

Model

VDI 450-8

| | |
|--------------------------|-------|
| Selections / Columns | 8 / 8 |
| Max. product length (mm) | 505 |
| Max. product Ø (mm) | 69 |

Capacities:

| | | |
|------------|--------|-----|
| Can | 0,33 l | 448 |
| PET bottle | 0,50 l | 224 |

Dimensions and weights:

| | |
|----------------|------------------|
| H x W x D (mm) | 1615 x 790 x 940 |
| Weight | 280 kg |

Performance data:

| | |
|------------------------|---------------|
| Refrigeration | 520 W / 10cc |
| Power supply | 230 V / 50 Hz |
| Max. power consumption | 875 W |

| | |
|---------|--------------------------|
| Control | Executive; MDB |
| Cabinet | Zinc powder coated steel |

Standard:

- Black cabinet
- 5 digit display
- Safety coin return
- Cut out for validator or alternative payment system
- Lock
- Choice of neutral front poster

Options:

- Cabinet colour on request
- Two-line LCD display
- Security cash system
- Anti-vandalism panel in selection button area
- Safety sliding coin insert
- Anti-rain kit IP 34
- DEX / UCS interface
- Special coded lock
- Individual graphics



Vertrieb und Service durch:


ENGEL
 AUTOMATEN + TECHNIK

Asperger Str. 8 D-74321 Bietigheim-Bissingen
 Tel. 07142 / 9105-0 Fax 07142 / 9105-11
 Mail: info@engeltec.de www.engeltec.de

SandenVendo GmbH | Spangerstrasse 22 | D-40599 Düsseldorf

Fon: +49 (0)211-740 39-0 | Fax: +49 (0)211-748 85 41

Web: www.SandenVendo.com | e-Mail: infosvg@sandenvendo.com


Vendo
 SANDEN