

■ Different vend modules (to combine) for individual requirements

■ Maximum flexibility by modular structure

■ Easy programming using selection button sequence

■ Electronic control and data-recording

■ Energy management by real time clock

■ Electronically controlled forced air-cooling

■ 24 V D/C motors



Model	VDI 486
Selections / max. modules	10 / 6
Max. product length (mm),	368 ¹ , 350 ²
Max. product Ø (mm)	72 ¹ , 95 ²

Capacities per module:	Narrow S. ¹	Wide S. ²	Flapper ³
Can 0,33 l	51	88	48
PET bottle 0,50 l	17	28	--
PET bottle 1,00 l	--	24	--
Carton brick pack 0,25 l	--	--	84
brick pack 0,33 l	--	--	60
0,33 Module	Max. H x W (in mm): 143 x 69,85		
0,5 Module	Max. H x W (in mm): 177,8 x 69,85		

Dimensions and weights:

Width module (mm)	120 ¹	132-185 ²	175 ³
Available interior space (mm)			780
H x W x D (cabinet mm)			1830 x 855 x 815
Weight			320 kg

Performance data:

Refrigeration	0,899 kW
Power supply	230 V / 50 Hz
Max. power consumption	820 W

Control	Executive; MDB
Cabinet	Zinc coated steel, powder painted

Standard:

Black cabinet
 5 digit display
 Safety coin return
 Anti-vandalism panel in
 selection button area
 Cut out for validator or
 alternative payment system
 Lock
 Choice of neutral front poster

Options:

Cabinet colour on request
 Two-line LCD display
 Security cash system
 Safety sliding coin insert
 Anti-rain kit IP 34
 Loading rack
 DEX / UCS interface
 Special coded lock
 Individual graphics

Vertrieb und Service durch: